

Product sheet

Picture Combiner BT03M



Article-Number: 300512

Short description:

- Digital image separator vertical or horizontal
- 19" cassette
- Two full screen buffers
- Optocoupler input for switching
- Channel texts for each input
- Displacement
- Reflection

Specification

System	CCIR / PAL, Option: NTSC
Resolution	720 x 576
Operational voltage	24V DC
Power input	10W
Number of camera inputs	2 entkoppelte Durchschleifeingänge
Number of screen outputs	2
Camera connections	BNC
Camera Input	1 Vpp, FBAS, 75 Ohm
Screen connections	BNC
Screen output	1 Vpp, FBAS, 75 Ohm
Voltage connection	Wago 3 pol. 721-133 (at Backplane Art.Nr. 501152)
Switch-/Alarm connection	Cage Clamp (at Backplane Art.Nr. 501152)
Switch-/Alarm inputs	2
Switch-/Alarm outputs	1
Interface	RS488 (SubD 9)
Temperature range (operating)	-25° to +75 °C
Temperature range (storage)	-50° to +85 °C
Casing	Aluminium
Casing enclosure type	IP 20
Dimensions (W x H x D)	61 mm x 129mm x 160mm (12TE/3HE)
Weight	1,000g

Meets the following railway standards:

Climate-proof and shake-proof	EN 50155
Electro-magnetic compatibility (EMC)	EN 50121-3-2:2000

All information provided in this product sheet refers to the current conditions and may be subject to change.