

Product sheet

SIUS^e-IP



Article-Number: 300533

Short description:

- Digital Video-IP Recorder
- Master controler of Video-IP server

Main features:

- Digital recording on removable hard disc
- MJPEG image compression
- Internal clock
with adjustment for daylight saving time
- 8 gate inputs / 4 gate outputs
- Image transmission over Ethernet possible

Specification:

Recording medium	2,5" Removable hard disc
System	Linux
Image compression	MJPEG
Operational voltage	110V DC
Power input	From 30W depending on specification
Voltage output for cameras	12V DC / 4A
Outputs	4 relay outputs potential-free
Inputs	8 potential-free
Screen output	VGA
Recording speed	max. 100 frames/s @ 35kB/frame
Interface	RS485 (SubD 9)
Interface	VDV-IBIS-Interface (SubD 9)
Interface	2 x Ethernet 10/100 MBit LAN (M12)
Interface	2 x USB
Temperature range(operating)	-25° to + 75 °C
Temperature range(storage)	-50° to + 85 °C
Casing	Aluminium
Casing enclosure type	IP20
Dimensions (W x H x D)	321mm x 134mm x 285mm (63TE/3HE)
Total weight	5.700g



Product sheet

SIUS^e-IP

Meets the following railway standards:

Climate-proof and shake-proof	EN 50155
Electro-magnetic compatibility (EMC)	EN50121-3-2:2006

All information provided in this product sheet refers to the current conditions and may be subject to change.