



Product sheet

TFT-Display DCE 102-15,0



Article Number: 501158

Short description:

- display for surveillance
- small buildsize

Specification

Display	15,0" XGA TFT LCD
Resolution in pixel	1024 horizontal / 768 vertical
Pixel size	0,279 mm x 0,279 mm
Active surface	304,1 mm x 228,0 mm
Contrast ratio typ.	700:1
Brightness typ.	400 cd/m ²
Viewing angle	up 80° down 80° right 80° left 80°
Response time	T _R = 8 ms / T _F = 17 ms
Backlight	CCFL
Operational voltage	12 V DC
Power input	1,5 A
Enclosure type	IP 54 Front / IP 20 Back
Temperature range (operating)	-25° to + 75 °C
Temperature range (storage)	-50° to + 85 °C
Humidity	90% non-condensing
Interfaces:	
X1 Power input	D-Sub 7W2 / male
X2 Video input I	BNC / FBAS 1 VSS / 75 Ohm / female
X3 Video input II	VGA / Sub-HD / 15 pol. / female
X4 Video input III	DVI – Option
Casing	Aluminium
Colour	RAL 9005 (deep black / powder-coated / fine structure)
Dimensions (W x H x D)	425 x 333 x 85
Total weight	4.000 g



Product sheet

TFT-Display DCE 102-15,0

Meets the following railway standards:

Climate-proof and shake-proof	EN 50155 T3
Electro-magnetic compatibility (EMC)	EN50121 -3-2:2000

All information provided in this product sheet refers to the current conditions and may be subject to change.