



Product sheet

Mobile Video Crossbar VKS09M 8/8/4



Article-Number: 501379

Short description:

- Video-Matrix sharing up to 8 cameras to 4 displays, 8 feed-through inputs
- Videosignal control
- RS422 interface for remote control
- Update via serial interface
- Text via On-Screen-Display

The **VKS09M** is a video crossbar for sharing different video sources (such as cameras) to different video outputs (such as Displays, Digital recorder etc.).

Specifications

System	PAL / NTSC
Voltage	24 V DC
Power input	max. 1 A
Quantity of video inputs	8 BNC
Quantity of feed-through inputs	8 BNC
Quantity of video outputs	4 BNC decoupled
Video input level / impedance	FBAS 1 Vss, 75 Ohm
Video output level / impedance	FBAS 1 Vss, 75 Ohm
Status signals	3 LED
Interface 1	Power
Interface 2	RS 422 for control and service
Operating temperature range	-25° to +70° C
Storage temperature range	-40° to +85° C
Humidity	Up to 90 % non-condensing
Case material	Aluminium
Case protection class	IP 20
Dimensions W x H x D	107 x 130 x 234 mm (21 HP/ 3 RU)
Weight	1.440 g



Product sheet

Mobile Video Crossbar VKS09M 8/8/4

Meets the following standards:

Climate- and shake- resistance	EN 50155
Electromagnetical compatibility (EMC)	EN 50121-3-2
Fire prevention	DIN 5510/3

Accessories:

<i>Article Number</i>	<i>Description</i>
500544	RS232/RS485-RS422-converter incl. power-supply

All information provided in this product sheet refers to current conditions and may be subject to change.