

# Product sheet

## SIUSeIP12



**Article Number: 501598**

**Short description:**

- Digital Video-IP Recorder
- Extern Back-Up Battery

**Specification**

Operating System	Linux
Recording medium	Removable disk SSD
Video-Compression	H.264
Recording speed	max. 8 x 25fps @ 4CIF
Recording period	Depending on numbers of cameras, clock cycle and capacity removable disk
Voltage output	12V DC
Power input	ca. 90W depending on specification
Temperature (range)	-25° to + 75 °C
Temperature (storage)	-50° to + 85 °C
Initialization time	ca. 60 sec.
Humidity	max. 90% non-condensing
Protection class	IP20
<b>Interfaces</b>	
X1 (Power Input 12 V DC)	COMBICON/MSTB/2pol./female
X2 USB1	SUB-D/9pol./female
X3 Audio	SUB-D/9pol./female
X4 USB2	SUB-D/9pol./female
X5 (LAN1 ) 10/100MBit	M12/d-codiert/4pol./female
X6 (LAN2) 10/100MBit	M12/d-codiert/4pol./female
X7 Service (VGA Monitor)	HD 15/female
X8 Backup battery	SUB-D/15pol./male
X9 USB3	SUB-D/9pol./female
Speech	German / English
Casing	19" cassette, Aluminium, partial slot for 19" component assembly according to DIN 41494
Maße W x H x D	213.4mm x 128.4mm x 285mm (42TE/3HE)
Total weight	2,300g without removable disk
<b>Meets following standards:</b>	
Climate-proof and shake-proof	EN 50155
Electro-magnetic compatibility (EMC)	EN 50121-3-2

All information provided in this production sheet refers to the current conditions and may be subject to change.