

Product sheet

Picture Combiner 16



Article Number: 501784

Short description:

- Digital image separator, vertical/horizontal separation configurable
- Two full screen buffers
- Channel texts for each input
- Displacement
- Reflection
- Optocoupler input for switching
- Webinterface for configuration and service
- 19" cassette

Specification

System	CCIR / PAL, Option: NTSC
Resolution	704 x 576
Operational voltage	24V DC rated voltage (10V-36V)
Power input	about 6W
Number of screen inputs	2 decoupled loop through inputs
Number of screen outputs	2
Camera connections	BNC
Camera input	1 Vss, FBAS, 75 Ohm
Screen connections	BNC
Screen output	1 Vss, FBAS, 75 Ohm
Voltage connection	D-Sub with high-current contacts, 2W2C
Switch-/Alarm connection	D-Sub 9pol.
Switch-/Alarm inputs	2 via Optocoupler
Switch-/Alarm outputs	1 via Optocoupler
Interface	RS485 (SubD 9)
Temperature range (operating)	EN50155 T3
Temperature range (storage)	-40° to +85°C
Casing	Aluminium
Casing enclosure type	IP 20
Dimension (W x H x D)	(3HE/12TE) 129mm x 61mm x 167mm
Weight	600g

Erfüllt folgende Bahnnormen:

Climate-proof and shake-proof	EN 50155:2007+Cor.2010
Electro-magnetic compatibility (EMC)	EN 50121-3-2:2015

All information provided in this product sheet refers to the current conditions and may be subject to change.