

Product sheet

IP-Indoor Camera



Short description:

- IP-Indoor Camera with H.264 video compression
- 1/3" progressive scan CMOS
- 1.3 megapixel resolution
- Day / Night auto switch
- Vandalism resistant
- Camera complies with protection class IP 54

Specification

Recording sensor	1/3" Progressive Scan CMOS
Video Compression	H.264
Bitrate	32 Kbps to 16 Mbps
Lens	4 mm F1.8, opening angle ca.: 68° (H), 51° (V)
Picture elements	1280 x 960
Picture per second (fps)	max. 30fps (1280 × 960), max. 30fps (1280 × 720)
Linear Shutter (ESC)	1/30 to 1/100.000 sec.
Operational voltage	12 V DC
Power consumption	0.34 A
Protection type	IP 54
Temperature (range)	-25° to +70 °C
Temperature (storage)	-25° to +85 °C
Humidity	max. 91% non-condensing
Interface	
Ethernet	M12 d-codiert / 4 pol. / female
Voltage input	M12 a-codiert / 5 pol. / male
Camera casing	Zamak, Polycarbonat
Color	RAL 9003, powder coated
Dimensions W x H x D	99 x 97 x 47 mm (visible) (Installation depth of connector housing ca. 37 mm)
Lens angle adjustment	inclination: 0 - 90 °, rotation: ± 15 °
Total weight	430 g ± 20 g

Meets the following standards:

Climate-proof and shake-proof	EN 50155
Electro-magnetic compatibility (EMC)	EN50121-3-2:2000

All information provided in this product sheet refers to the current conditions and may be subject to change.